


DirectPatch Cat 6A UTP RJ 45 assemblies cables Technical Data Sheet

Patent Pending



Direct Patch Cat 6 RJ 45 Patch Cords:

PatchSee RJ 45 Patch Cords are designed, and individual tested for connecting the network equipment to patch panel and network user outlet. They are warranted for cat 6A TIA/EIA-568-B-2.10 Channel test for transmission frequencies of up to 500 MHz, and compatible with the 10 giga applications.

PatchSee Concept and main characteristics

- Light identification by plastic optical fiber,
- Lengths 20 (6.1 m) feet up to 100 (30 m) in standard lengths, and up to 165 feet (50 meters) on specific demand,
- Color cable: Black with white marking,
- Color boot: Grey with white marking,
- Movable color clip, 16 colors available,
- Packaging: boxes of 1 piece by box,
- Available in cross patch cord,
- Marking on the boot: length and P/N,
- Unique serial number marking on the cable,
- Warranty 25 years for Channel Cat 6A link,
- Individual tested: each Patch Cord is individual tested (Return Loss, Attenuation, NEXT, etc...) and all the reports tests are archiving on computer database.

Technical Data Sheet

Construction

Number of pairs	4
Type	U-UTP with plastic cross web
Conductor	Stranded bare copper wire
AWG	24
Insulation	Foam Skin Polyethylene
Individual pair screen	n a
Pair screen	n a
Optical wave guide	2 POF 0.5 mm up to 32 feet, 0.75 mm for length bigger than 32 feet
Drain	n a
Jacket	PVC Black with white printing
Overall diameter	6.2 mm
Plug housing	UL 1863 Polycarbonate 2 levels with management bar
Contacts	Moved contacts
Contact Plating	50 μ inches gold minimum (1.2 μ m)
Shielding	n a

Mechanical Properties of the cable

Fire Propagation Test	Temperature range During operation	Fire load	Bending radius
UL 444 VW 1 Flame test	-20°C up to +75°C	372 MJ/km	>25 mm without load

Electrical Properties of the cable (at 20°C +/- 5°C)

DC loop resistance	Insulation resistance (500V)	Capacitance at 800 Hz	Impedance 1-100MHz	Impedance 100-250MHz	Propagation delay	Test voltage (DC, 1 min)
< 340 Ω /km	> 2000 M Ω *km	Nom. 43nF/km	100 +/- 15 Ω	100 +/- 15 Ω	< 427 ns/100m	1000 V